

AM7915MZT - Edge



With the use of the latest, cutting-edge optics, a brand new 5 megapixel sensor and several special features, the Dino-Lite AM7915MZT is a marvel of technology and the best choice for the high-demanding professional. The Dino-Lite AM7915MZT offers superb image quality and color reproduction in a robust, compact and appealing housing.



USB 2.0



ADJUSTABLE
~10 - 220x



5 MEGAPIXEL
2592 x 1944



EXTENDED
DEPTH OF FIELD
EDOF



EXTENDED
DYNAMIC RANGE
EDR



AUTOMATIC
MAGNIFICATION
READING
AMR



POLARIZER
ANTI-REFLECTION
FLC



FLEXIBLE
LED CONTROL
FLC



EXCHANGEABLE
CAP

With the Extended Dynamic Range (EDR) feature, the details of darker or brighter areas within the object can be revealed by stacking images at different exposure levels. The Extended Depth of Field (EDOF) feature automatically stacks images at different focus level to improve the depth of field on rough or uneven surfaces. With the built-in automatic magnification reading (AMR), measurements can be performed easily and quickly. Because of the built-in polarization filter this model is ideal when working with shiny or reflective objects such as metal, plastic, glass, jewelry, electronics, etc.

The main features of the AM7915MZT are:

- 5 Megapixel Edge sensor
- Extended Depth of Field (EDOF)
- Extended Dynamic Range (EDR)
- Automatic Magnification Reading (AMR)
- Adjustable polarizer
- Flexible LED Control (FLC)
- And more...

Details

Dino-Lite range: Dino-Lite Universal

- **Lighting**

- Light/ LED type: White
- Number of LEDs: 8
- LED on/off switchable: Yes
- Infrared filter: IR cut-filter >650 nm
- Diffuser available: Yes (N3C-D included)
- Emission filter: No
- Polarizer: Yes, linear

- **Optics**

- Magnification: 10-220x
- Macro zoom: No
- Working distance: Standard
- Lens type: Glass with anti-reflection coating

- **Sensor**

- Sensor type: CMOS
- Resolution: 5 Megapixel (2592x1944)
- Maximum frame rate: 30 fps

- **Compatibility**

- Interface: USB 2.0
- Operating system: Windows XP, Vista, 7, 8 & 10, MacOS 10.9 and up
- Included software: DinoCapture 2.0 (Windows), DinoXcope (Mac OS)
- Supported image formats (Windows): BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX
- Supported video formats (Windows): WMV, FLV, SWF
- Supported image formats (MacOS): -
- Supported video formats (MacOS): -
- Imaging standards: DirectShow, UVC

- **Housing**

- Housing material: Metal housing
- Magnification lock: Yes
- Dimensions: 10.5cm (L) x 3.2cm (D)
- Weight: 137g
- Cable length: 1.8m

- **Features**

- Special feature: Aut. Magn. reading, Ext. Dynamic Range (EDR), Ext. Depth of Field (EDOF), Flexible LED Control (FLC)
- Measurement: Yes
- Calibration: Yes
- Microtouch sensor: Yes

- ESD safe: Yes

- **Information**

- Package contents:
Microscope, Carry pouch, Software CD, User manual, Quick guide, Calibration target, Front cover box
- Warranty information: 2 years European warranty
- Regulatory approval: CE, FCC, ROHS
- Working distance/ field of view/ depth of field:

Magnification Rate	Working Distance *	Field of View(x)	Field of View(y)	Depth of Field
10	136.0	37.8	28.3	-
20	60.2	19.5	14.6	2.5
30	33.5	13.0	9.7	1.8
40	20.9	9.8	7.3	1.5
50	13.9	7.8	5.8	-
60	9.7	6.5	4.8	-
70	7.1	5.6	4.2	1.0
80	5.5	4.9	3.6	-
90	4.5	4.3	3.2	-
100	4.1	3.9	2.9	-
110	4.0	3.6	2.7	-
120	4.1	3.3	2.4	-
130	4.5	3.0	2.2	-
140	5.0	2.8	2.1	-
150	5.6	2.6	1.9	-
160	6.3	2.4	1.8	-
170	7.1	2.3	1.7	-
180	8.0	2.2	1.6	-
190	8.9	2.1	1.5	-
200	9.9	2.0	1.5	-
210	10.9	1.9	1.4	-
220	11.9	1.8	1.3	0.1
Listed values may differ slightly	* Without front cap			Unit = mm

