



## **Laboratory Evaporation Glassware**

Decades of expertise in glass manufacturing

Original BUCHI glassware guarantees the highest levels of efficiency and safety thanks to outstanding precision in manufacturing. For more than 75 years BUCHI has been manufacturing innovative and durable glass parts to ease daily laboratory work.



## Glassware made by BUCHI

Benefit from high quality and precision

The BUCHI experience in glass manufacturing results in glassware of outstanding quality and guarantees highest safety and increased efficiency due to our exacting standards of accuracy.

### Benefits of BUCHI glassware



#### Highest efficiency

- Maximized vacuum stability thanks to very tight joints
- Optimum heat transmission due to optimized wall thickness of evaporating flasks
- High evaporating performance due to pear-shaped evaporating flask
- High throughput due to advanced design of condensers



#### Maximized safety

- Use of highly resistant glass provides highest levels of safety
- Guaranteed leak-tightness and protection against hazardous fumes thanks to high precision joints
- Maximum stability thanks to sophisticated PLASTIC+GLAS coating



#### Proven reliability

- More than 75 years of experience in glass manufacturing
- Durable products made with best quality raw materials
- Developed and manufactured by experienced and committed employees

## Laboratory evaporation glassware quality facts



### High quality materials

- Exclusive use of DURAN® borosilicate glass 3.3
- High chemical resistance against acids, alkalis and organic substances
- Resistant to thermal shocks and high temperatures combined with low thermal expansion



### Accuracy

- Constant monitoring of glass wall thickness uniformity
- High degree of attention paid to sphericity of rotating glass parts
- Glass parts are tension-relieved at 560 °C



### Expertise

- Unique machines developed in-house to automate repetitive manufacturing processes in order to guarantee a high level of reproducibility
- Many decades of experience guarantee top quality glass parts

## “PLASTIC+GLAS” coating



### Maximized safety

- Protects users from contact with chemicals in case of glass breakage
- Avoids risk of injuries when touching broken glass
- Prevents glass splitter impacts in case of implosions

### Improved sturdiness

- Protects glassware from physical damage
- Is chemical resistant high quality coating

### Retention of substances

- Retains valuable substance in case of glass breakage
- Valuable sample or toxic solvent vapors remain within glassware

### P+G properties




For standard applications. Available for condensers, evaporating and receiving flasks. Operating range: -30 to 60 °C



Low temperature receiving flasks are used for cold trap and other low temperature applications. Operating range: -70 to 40 °C

## Evaporating flasks

High performance pear-shaped flasks for distillation of solvents.



Evaporating flask




Evaporating flask, 5 L

Flask size	29/32	24/40	24/29	29/42
50 mL	000431	008750	000472	008736
50 mL P+G	033405			
100 mL	000432	008751	000473	008737
100 mL P+G	033404			
250 mL	000433	008754	008753	008738
250 mL P+G	025520			
500 mL	000434	008758		008739
500 mL P+G	025322	025261		
1000 mL	000435	000440	008761	008762
1000 mL P+G	020729	020730		025517
2000 mL	000436	008765	008764	008769
2000 mL P+G	025323	025262		
3000 mL	000437	008767		008770
3000 mL P+G	025324	025263		027346
4000 mL	047991	047990		
4000 mL P+G	047993	047992		
5000 mL <sup>1</sup>	046573	046586		
5000 mL P+G <sup>1</sup>	046583	046596		

<sup>1</sup>Spherical

## Drying flasks

Pear shaped flasks with indents for increased efficiency in powder drying by reducing accumulations on the glass walls.




Drying flask

Flask size	29/32	24/40
500 mL	000452	011579
1000 mL	000453	000420
2000 mL	000454	011580

## Beaker flasks

Beaker flasks with large screw-cap opening for easy retrieval of substances. Drying beaker flask consists of notches for increased efficiency in powder drying. Both variations can be used in the temperature range from -40 to 100 °C.



Beaker flask

Flask size	For evaporation		For drying	
	29/32	24/40	29/32	24/40
500 mL <sup>1</sup>	11063154	11063155	11063158	11063159
1500 mL <sup>2</sup>	11063156	11063157	11063160	11063161

<sup>1</sup>Working volume of 150 mL    <sup>2</sup>Working volume of 450 mL

## Receiving flasks


Spherical flasks with ball joint (35/20) for collecting the condensed solvents.



Receiving flask

Flask size	Standard	P+G	P+G-LT
50 mL	000421		
100 mL	000422		
250 mL	000423	11060907	11060908
500 mL	000424	025264	040774
1000 mL	000425	020728	040775
2000 mL	000426	025265	040776
3000 mL	000427	025266	040777

Spherical flask with ball joint (35/20) and with manual drain valve for draining after aeration without removal of receiving flask.



Receiving flask with drain valve

Flask size	P+G
1000 mL	036919

## Flask holder

Holder for 50 mL to 5000 mL evaporating and receiving flasks.




Flask holder


Quantity	
1	048618
5	11059916

## Vapor ducts


Glass parts to connect the evaporating flask to the Rotavapor®. All vapor ducts include the Combi-Clip to fasten the evaporating flask.



Vapor duct



Vapor duct (analytical)



Vapor ducts

R-300, R-215, R-210, R II (with Combi-Clip\*) Compatible with glass assembly

	29/32	24/40	29/42	24/29
A	11062267	11062268	11062269	
V, C, S, E, CR, BY	11062186	11062187	11062464	11062909
V, C, S, E, CR, BY (analytical)	11062465	11062466	11062467	

For high temperatures, short Combi clip, vapor duct HT, ring NS 34/32 on 30/32

11061837

Vapor duct with frit SJ29/32, incl. Combi-Clip

11057297

For powder drying. To prevent powder from getting into the condenser. For glass assembly V, C, S, E, BY and CR.

\*Single Combi-Clip: 11059770

R-100, R-3, R-3000, R-144, R-134, R-124, R-114

Compatible with glass assembly

	29/32	24/40
V and C	032339	032341

## Vacuum seals

Air-tight lip seals between the rotating vapor duct and the condenser.




Vacuum seal

Compatibility	Vacuum seal	
R-300, R-215, R-210, R II	WD26, seal PTFE <sup>1</sup>	048021
R-100, R-3	KD22, seal PTFE	000636
R-100, R-3	KD22, seal PTFE <sup>1</sup>	11056622


<sup>1</sup>FDA-compliant sealing material

## Stopcocks

Glass parts for aerating the Rotavapor® system.



Standard stopcock



Stopcock 3-way valve


Stopcock	18.8/38
Standard stopcock	040627
Professional stopcock (less contamination)	000637
Stopcock PTFE 3-way valve (no grease needed)	11058814

## Bump trap adapters

Glass adapters for excessively-foaming samples. Prevents foam from entering the vapor duct and condenser.



Reitmeyer




Bump trap

Type	29/32	24/40	Length
Reitmeyer	036576		135 mm
Reitmeyer		036577	150 mm
Bump trap	11056920		160 mm
Bump trap		11056919	175 mm


## Distillation spiders

Glass parts for simultaneous distillation in 5, 6, 12 or 20 distilling flasks (cross contamination possible). Please refer to the BUCHI "Parallel Evaporation Solutions" brochure for highly efficient parallel evaporation without cross contamination.



Spider with evaporating flasks

Spider with evaporating flasks	29/32 <sup>1</sup>	24/40 <sup>1</sup>	24/29 <sup>2</sup>
Spider with 5 x 50 mL flasks (24/29)	001332	011574	
Spider with 5 x 100 mL flasks (24/29)	001333	011575	
1 x 50 mL evaporating flask (without spider)			000472
1 x 100 mL evaporating flask (without spider)			000473



Spider with cylindric flasks


Spider with cylindric flasks	29/32 <sup>1</sup>	14/23 <sup>2</sup>
Spider with 6 x 20 mL cylindric flasks (14/23)	001334	
Spider with 12 x 20 mL cylindric flasks (14/23)	001335	
Spider with 20 x 20 mL cylindric flasks (14/23)	001336	
1 x 20 mL cylindric flask (without spider)		000477

<sup>1</sup> Joint of the spider to vapor duct    <sup>2</sup> Joint of the flask to spider

## Intermediate piece



Intermediate piece with valve



Set Rotavapor connection

Connection piece with 3-way valve, placed between the condenser and the receiving flask. Allows to remove and empty the receiving flask during evaporating process. 11063430

Combining the Multivapor with the Rotavapor requires a T-shaped glass connector for the condenser of the rotary evaporator. The T-piece consist of two spherical joints for the condenser assembly and a SVL 22 joint for the vacuum tube. The length of the tube is 400 mm. 048740



## Rotavapor® glass assemblies

Widest range of highly efficient condensers



	A	C	V	S	CR	E	BY
	Diagonal	Cold trap	Vertical	Reflux	Cold trap reflux	Expansion	Double jacket
<b>Applications</b>							
Distillation	•	•	•	•	•	•	•
Drying	•	•	•	•	•	•	•
Concentration	•	•	•	•	•	•	•
Reflux reaction				•	•		•
Soxhlet extraction				•			•
Re-crystallization	•	•	•	•	•	•	•
<b>Solvent/Sample properties</b>							
Boiling point range	M – H	L – M	M – H	M – H	L – M	M – H	M – H
Bumping or foaming	• <sup>1</sup>	• <sup>1</sup>	• <sup>1</sup>	• <sup>1</sup>	• <sup>1</sup>	•	• <sup>1</sup>
<b>Characteristics</b>							
Cooling	CL	CM	CL	CL	CM	CL	CL
Cooling temperature range	H	M	H	H	M	H	H
Suitable for high throughput	•		•	•		•	•
Vapor temperature sensor			Available	Available		Available	Available
Foam sensor		•	•	•	•		•
Automatic distillation			• <sup>2</sup>	• <sup>2</sup>			
Suitable for limited space	VS	HS	HS	HS	HS	HS	HS
Condenser surface max. [cm <sup>2</sup> ]	1500	500	1500	1500	1500	500	1300
Available for R-300	•	•	•	•	•	•	•
Available for R-100		•	• <sup>3</sup>				


H = High M = Medium L = Low VS = Limited vertical space HS = Limited horizontal space  
 CL = Cooling liquid CM = Coolant mixtures (e.g. dry-ice/acetone)

<sup>1</sup> With Reitmeier adapter <sup>2</sup> Possible with AutoDest sensor only <sup>3</sup> Limited features



## Vertical (V) condenser

The following features displayed are only applicable to the condenser compatible to the Rotavapor® R-300.



## Glass assemblies

All glass assemblies include a 1 liter receiving flask, the required tubings and a ball joint clamp. Evaporating flask, vacuum seal, vapor duct and condenser holder are not included.

Characteristics	R-100					R-300			
	V	C	A	V	C	CR	S	E	BY
Top inlet			•	•			•	•	•
Inner glass tube				•			•		
Stopcock (feeding possible)	•	•	•	•	•	•	•	•	•
Inner glass plate				•					
Connector for vapor temperature sensor				•			•	•	•
Condenser holder*	052893	052893		048180	048180	048180	048180	included	048180
Condensate trap				•					


\*Optionally available

### Part no. of glass assemblies


	V	C	A	CR	S	E*	BY
R-300, R-2xx, R-1xx	11062432	040640	048168	048292	048290	11061112	048176
P+G: R-300, R-2xx, R-1xx	11062433	040642	048169	048293	048291	11061113	048297
R II	048172	040640	048170				
P+G: R II	048173	040642	048171				
R-100, R-3	11057056	040640					
P+G: R-100, R-3	11057057	040642					

\*Not compatible with R-100

#### What is the chimney effect and how does it affect distillation efficiency?



Chimney effect




Turbulence, forced condensation

By evaporation - changing of state from liquid to gas - the volume of the sample increases by a factor up to 20,000. In the condenser the gas is re-condensed to a liquid and the volume shrinks immediately. During this evaporation-condensation process, vapor velocity at narrow points of the glass apparatus can be up to 150 km/h.

Distillation efficiency can be significantly increased by reducing the so-called chimney effect.

In order to maximize turbulence inside the condenser, the vacuum is applied at the top middle, however, the vacuum connectors are below. This optimal construction maximizes the movement of vapor inside the condenser, thus preventing fumes escaping to the vacuum source.

#### Can the evaporation flask be fed via the condenser stopcock?



Standard stopcock



Screw cap

Yes, all condensers used for R-300, R-100, R-210, R-215 and R-3 allow feeding of the evaporation flask through the standard stopcock. The C- and A-condenser for R II consist of a screw-cap instead of a stopcock and therefore does not allow feeding; a stopcock for feeding is optionally available.

#### Are the condensers shown on the previous page compatible with the older generation of BUCHI Rotavapor® product lines (R-215, R-210, R II, R-3)?

Yes, the glass assemblies V, C and A are compatible with the current generation BUCHI Rotavapor®. Glass assemblies CR, S, E and BY are compatible with the product lines R-300, R-210 / R-215 and R II only. It is recommended to also obtain a support rod (condenser holder) for glass assemblies V, C, CR, S and BY.

## What factors influence glass shock temperature?

---

DURAN® borosilicate glass 3.3 is notable for its excellent temperature stability. The shock temperature is influenced by many stress factors which act cumulatively. Typical factors are tensions, vacuum, mechanical damage and shape as well as thickness of the respective glass part. Glass should be inspected visually prior to any use, especially when applying vacuums.


## Are there differences between BUCHI and 3rd party evaporating flasks?

---

Yes, there may be several properties which set high quality BUCHI flasks apart: Optimized/uniform flask thickness, quality of joints and sphericity of the flask. All of these properties have an important impact on distillation efficiency.

## What do the numbers “29/32” shown on previous pages mean?

---



The number-pair (e.g. 29/32) describes a joint size. The first number refers to the width of the joint (A). The second number (after the slash) refers to the length of the joint (B). 29/32 therefore means that the width of the joint is 29 mm and the length of the joint is 32 mm.

## Can BUCHI provide customized glassware which is not listed in this document?

---

Yes, there is an additional extensive range of glassware available. BUCHI also offers customized glass according to your needs, for example amber glass for light-sensitive samples. For further information about our glassware range please contact your local BUCHI representative.

## BUCHI Affiliates:

### Europe

<b>Switzerland/Austria</b> <b>BÜCHI Labortechnik AG</b> CH – 9230 Flawil T +41 71 394 63 63 F +41 71 394 64 64 buchi@buchi.com www.buchi.com	<b>Benelux</b> <b>BÜCHI Labortechnik GmbH</b> Branch Office Benelux NL – 3342 GT Hendrik-Ido-Ambacht T +31 78 684 94 29 F +31 78 684 94 30 benelux@buchi.com www.buchi.com/bx-en	<b>France</b> <b>BUCHI Sarl</b> FR – 94656 Rungis Cedex T +33 1 56 70 62 50 F +33 1 46 86 00 31 france@buchi.com www.buchi.com/fr-fr	<b>Germany</b> <b>BÜCHI Labortechnik GmbH</b> DE – 45127 Essen T +800 414 0 414 0 (Toll Free) T +49 201 747 49 0 F +49 201 747 49 20 deutschland@buchi.com www.buchi.com/de-de
<b>Italy</b> <b>BUCHI Italia s.r.l.</b> IT – 20010 Cornaredo (MI) T +39 02 824 50 11 F +39 02 575 12 855 italia@buchi.com www.buchi.com/it-it	<b>Russia</b> <b>BUCHI Russia/CIS</b> Russia 127287 Moscow T +7 495 36 36 495 russia@buchi.com www.buchi.com/ru-ru	<b>United Kingdom</b> <b>BUCHI UK Ltd.</b> GB – Oldham OL9 9QL T +44 161 633 1000 F +44 161 633 1007 uk@buchi.com www.buchi.com/gb-en	<b>Germany</b> <b>BÜCHI NIR-Online</b> DE – 69190 Walldorf T +49 6227 73 26 60 F +49 6227 73 26 70 nir-online@buchi.com www.nir-online.de

### America

<b>Brazil</b> <b>BUCHI Brasil Ltda.</b> BR – Valinhos SP 13271-200 T +55 19 3849 1201 F +55 19 3849 2907 brasil@buchi.com www.buchi.com/br-pt	<b>USA/Canada</b> <b>BUCHI Corporation</b> US – New Castle, DE 19720 T +1 877 692 8244 (Toll Free) T +1 302 652 3000 F +1 302 652 8777 us-sales@buchi.com www.buchi.com/us-en
---	--

### Asia

<b>China</b> <b>BUCHI China</b> CN – 200052 Shanghai T +86 21 6280 3366 F +86 21 5230 8821 china@buchi.com www.buchi.com/cn-zh	<b>India</b> <b>BUCHI India Private Ltd.</b> IN – Mumbai 400 055 T +91 22 667 75400 F +91 22 667 18986 india@buchi.com www.buchi.com/in-en	<b>Indonesia</b> <b>PT. BUCHI Indonesia</b> ID – Tangerang 15321 T +62 21 537 62 16 F +62 21 537 62 17 indonesia@buchi.com www.buchi.com/id-in	<b>Japan</b> <b>Nihon BUCHI K.K.</b> JP – Tokyo 110-0008 T +81 3 3821 4777 F +81 3 3821 4555 nihon@buchi.com www.buchi.com/jp-ja
<b>Korea</b> <b>BUCHI Korea Inc.</b> KR – Seoul 153-782 T +82 2 6718 7500 F +82 2 6718 7599 korea@buchi.com www.buchi.com/kr-ko	<b>Malaysia</b> <b>BUCHI Malaysia Sdn. Bhd.</b> MY – 47301 Petaling Jaya, Selangor T +60 3 7832 0310 F +60 3 7832 0309 malaysia@buchi.com www.buchi.com/my-en	<b>Singapore</b> <b>BUCHI Singapore Pte. Ltd.</b> SG – Singapore 609919 T +65 6565 1175 F +65 6566 7047 singapore@buchi.com www.buchi.com/sg-en	<b>Thailand</b> <b>BUCHI (Thailand) Ltd.</b> TH – Bangkok 10600 T +66 2 862 08 51 F +66 2 862 08 54 thailand@buchi.com www.buchi.com/th-th

## BUCHI Support Centers:

<b>South East Asia</b> <b>BUCHI (Thailand) Ltd.</b> TH-Bangkok 10600 T +66 2 862 08 51 F +66 2 862 08 54 bacc@buchi.com www.buchi.com/th-th	<b>Middle East</b> <b>BÜCHI Labortechnik AG</b> UAE – Dubai T +971 4 313 2860 F +971 4 313 2861 middleeast@buchi.com www.buchi.com	<b>Latin America</b> <b>BUCHI Latinoamérica Ltda.</b> BR – Valinhos SP 13271-200 T +55 19 3849 1201 F +55 19 3849 2907 latinoamerica@buchi.com www.buchi.com/es-es
---	--	--

We are represented by more than 100 distribution partners worldwide.  
 Find your local representative at: [www.buchi.com](http://www.buchi.com)

