

Lovibond® Water Testing

Tintometer® Group



TRA 500 Spectrophotometer

Measure Liquids, Gels and Powders with the TRA (Adaptor) Series



- Not Everything is Flat, Not Everything is Solid
- Awkward Objects Can Be Difficult to Measure
- The TRA (Accessory) is a Precision Engineered Portable Docking Station for the TR Range of Handheld, Sphere, Versatile Spectrophotometers
- Provides a Light Controlled Environment for the Measurement of Liquids, Gels and Powders

Part Number:

TRA 500 Spectrophotometer

The TRA series have been designed according to precision engineering as the ideal adaptor for the Lovibond® range of spectrophotometers. The robust shape makes them ideal for use in any laboratory. The angled viewing panel makes measurements easy-to-read. The integral lid blocks any ambient light since no external light interferes with the measurements.

Technical Data

Colour Type	Opaque
Light Source	Combined LED Light, UV Light
Optical Geometry	Reflect: di: 8°, de: 8° (diffused illumination, 8 degree viewing angle)
Integrating Sphere Size	48 mm
Spectrophotometric Mode	Concave Grating
Sensor	256 image Element Double Array CMOS Image Sensor
Display	3.5 inch TFT colour LCD, Capacitive Touch Screen
Interfaces	USB Bluetooth 4.0
Spectral Interval	10 nm
External Storage	2000 Standards : 20000 Samples
Measurement Mode	Single Measurement, Average Measurement
Power Supply	Li-ion Battery
Battery Life Time	5000 measurements with 8 hours
Location Method	Camera View Finder Locating

Measured Reflectance Range	0 - 200 %
Measurement Time	2.6 s
Measuring Aperture	Dual Aperture: 10mm/8mm & 5mm/4mm
Specular Component	SCI & SCE
Colour Difference Formular	ΔE^*ab , ΔE^*uv , ΔE^*94 , ΔE^*cmc (2:1), ΔE^*cmc (1:1), ΔE^*00v , ΔE (Hunter)
Other Colorimetric Index	WI (ASTM E313, CIE/ISO, AATCC, Hunter) YI (ASTM D1925, ASTM 313, TI (ASTM E313, CIE/ISO) Metamerism Index MI, Staining Fastness, Colour Fastness, Colour Strength, Opacity
Displayed Data	Spectrogram/Values, Samples Chromaticity Values, Colour Difference Values/Graph, PASS/FAIL Result, Colour Offset
Inter Instrument Agreement	MAV/SCI: $\Delta E^* \leq 0.15$
Bandwidth	10 nm
Repeatability	MAV/SCI: $\Delta E^* \leq 0.03$
Illuminants	CIE Illuminant D65 CIE Illuminant A CIE Illuminant C CIE Illuminant D50 CIE Illuminant D55 CIE Illuminant D75 CIE Illuminant F1 CIE Illuminant F2 CIE Illuminant F3 CIE Illuminant F4 CIE Illuminant F5 CIE Illuminant F6 CIE Illuminant F7 CIE Illuminant F8 CIE Illuminant F9 CIE Illuminant F10

	CIE Illuminant F11 CIE Illuminant F12
Portability	Portable
Illuminant Life Span	5 years, more than 3 million measurements
Observer	2° / 10°
Environmental Conditions	0 - 40 °C, 0 - 85° Relative Humidity (non condensing), Altitude < 2000 m
Stock Conditions	-20 - 50 °C, 0 - 85° Relative Humidity (non condensing)
Languages User Interface	English, German, French, Spanish, Portuguese, Chinese
Dimensions	184 x 105 x 77 mm
Weight	600 g

Delivery Scope

- Complete TR 520 or 500 kit (including power supply and calibration foot).
- TR Accessory (including sample cover).
- White background plate.
- 10, 20 and 30mm Optical Glass cells.

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
Fax: +49 (0)231/94510-30
sales@tintometer.de
www.lovibond.com
Germany

Tintometer China

Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@tintometer.us
www.lovibond.com
USA

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
water.sales@tintometer.com
www.lovibond.com
UK

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebu Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@tintometer.com
www.lovibondwater.in
India

Tintometer AG

Hauptstraße 2
5212 Hausen AG
Tel.: +41 (0)56/4422829
Fax: +41 (0)56/4424121
info@tintometer.ch
www.tintometer.ch
Switzerland

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@tintometer.com.br
www.lovibond.com.br
Brazil

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain