

## EH Heating Immersion Circulator

### Basic models for routine and standard applications -20°C...150°C

Heating Immersion Circulator for any bath tanks up to 50 liters JULABO Heating Immersion Circulators are available for various bath tanks up to a capacity of 50 liters and come equipped with a bath clamp that fits onto all tanks with a wall thickness up to 26 mm. This clamp allows fast and problem-free assembling for existing as well as new bath tanks. The immersion depth is 16.5 cm (adjustable down to 14.5 cm). The immersed parts are made of high-quality stainless steel or plastic. The pump set, which is available as an accessory, provides pumping to external systems for provision of external temperature tasks. An integrated cooling coil for cooling-water connection is also available as an accessory.



### Your advantages

- Bright LED temperature display, resolution 0.1 °C
- Keypad for setpoint, switches automatically to the actual value
- PID1 temperature control
- Adjustable high temperature cut-out
- Low liquid level protection
- ATC 1-point calibration
- Timer function

### Technical Data

Order No.	9118000
Model series	Economy
Category	Heating Immersion Circulators
Working temperature range (°C)	+20 ... +150
Temperature stability (°C)	0.03
Setting / display resolution	0.1 °C
Temperature Display	LED
Heating capacity (kW)	2
Pump capacity flow rate (l/min)	15
Pump capacity flow pressure (bar)	0.35
Ambient temperature	5...40 °C
Dimensions W x L x H (cm)	13 x 15 x 33
Weight (kg)	3.3
Classification according to DIN12876-1	Classification III (FL)according to DIN 12876-1
Cooling coil	optional
Usable immersion depth (cm)	8-14.5
Available voltage versions	230 V / 50 Hz 115 V / 60 Hz 100 V / 50-60 Hz 230 V / 60 Hz

For temperature applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.

## Characteristics

### Display



#### Easy to read

Large LED temperature display for actual value and setpoint (resolution 0.1 °C)

### Operation



#### Clear and simple

3-key operation for easy setpoint adjustment

### Temperature Control



#### Precise

PID Temperature control with set control parameters, temperature stability  $\pm 0.02 \dots \pm 0.2$  °C



#### High measuring accuracy

'Absolute Temperature C alibration' for manual compensation of a temperature difference, 1-point calibration

### Warning & Safety Functions



#### Protective functions

Adjustable high temperature cut-off or dry-running protection



#### For flammable bath fluids

Classification III (FL) according to DIN 12876-1

#### JULABO Contact

JULABO GmbH  
Eisenbahnstr. 45  
77960 Seelbach / Germany

Tel. +49 (0) 7823 51-0  
info.de@julabo.com

#### JULABO Services

Product finder, Accessory search, 1 PLUS Warranty, Catalog download, Callback service, Operating manuals, Safety data sheets, Software and more

[www.julabo.com](http://www.julabo.com)