

The image features a laboratory setting with a white Thermo Scientific Heratherm Microbiological Incubator in the foreground. The incubator has a digital display on the top right of its door, showing '37.0'. The door is open, revealing two shelves inside. In the background, there are several glass beakers and petri dishes on a lab bench. The beakers contain liquids of various colors (pink, orange, blue). The petri dishes contain agar plates with visible bacterial growth. The overall scene is brightly lit, with a soft purple and blue color palette.

Thermo Scientific Heratherm
Microbiological Incubators

Safe,
easy and efficient

Thermo
SCIENTIFIC

Thermo Scientific Heratherm Microbiological Incubators



your samples

We are obsessed with sample integrity. Each of our new laboratory microbiological incubators is designed with sample protection as top priority.


our obsession

Heratherm® microbiological incubators are available in four different models, providing three different incubator airflow technologies in a choice of six sizes.

- **Compact**
- **General Protocol**
- **Advanced Protocol**
- **Advanced Protocol Security**



Thermo Scientific Heratherm microbiological incubators family includes optional stainless steel models. All units are **CE** marked.



Discover why laboratories across the globe rely on Thermo Scientific products every day.

Successful incubation is dependent upon the environmental conditions. As such, you need to trust that your valuable samples are maintained in a safe and efficient manner.

Heratherm microbiological incubators are designed to provide long-term performance with optimal conditions – and are backed by a two-year warranty on parts and labor, meaning confidence for your investment.*

*Subject to Thermo Fisher Scientific Standard Limited Warranty. See www.thermofisher.com or product literature for details.

safe

- Safe view of samples through internal glass door, without impact on temperature
- Safe conditions with superior temperature uniformity
- Safe containment with automatic overtemperature alarm
- Alarm for temperature deviations

easy

- Easy temperature setting with intuitive user interface
- Easy to remove shelf system
- Easy to clean interior with rounded corners
- Easy to read large display

efficient

- Efficient small footprint to optimize benchtop space
- Conveniently stackable without the need for tools or stacking kits
- Efficient utilization of interior with flexible shelf system

Innovative technology for outstanding versatility



FEATURES	COMPACT INCUBATOR		GENERAL PROTOCOL INCUBATORS		ADVANCED PROTOCOL INCUBATORS		ADVANCED PROTOCOL SECURITY INCUBATORS	
	table top		table top	large capacity	table top		table top	large capacity
Temperature range	17 - 40 °C		ambient +5 °C - 75 °C		ambient +5 °C - 105 °C		ambient +5 °C - 105 °C	
Convection technology	Mechanical		Gravity		Dual		Dual Mechanical	
Fan speed adjustable	•		•		6 speeds		6 speeds gentle / fast	
Rounded corners	✓		✓		✓		✓	
Microprocessor control	✓		✓		✓		✓	
Automatic overtemperature alarm	•		✓		✓		✓	
Access port	•		✓		✓		✓	
Stackable	•		✓		✓		✓	
Stainless steel interior	•		1.4016		1.4301		1.4301	
RS232 interface	•		✓		✓		✓	
Internal glass door	•		✓		✓		✓	
Easy calibration routine	•		✓		✓		✓	
Timer: weekly / daily / real time	•		•		✓		✓	
Dry alarm contact for connection of alarm device	•		•		✓		✓	
Optional stainless steel exterior	•		•		✓		✓	
Certified decontamination cycle	•		•		•		✓	
Automatic undertemperature alarm	•		•		•		✓	
Door alarm	•		•		•		✓	
Lockable door	•		•		•		✓	
Connection for optional sample temperature sensor	•		•		•		✓	

Three different airflow technologies

Gravity convection

provides gentle airflow, with minimized drying out of samples. The best choice for applications with open plates, or open containers.

NEW! Dual convection

is a new unique technology which allows the operator to choose the fan speed – from 0% (which equals gravity convection) up to 100%. Depending on the application, the speed can be adapted to provide optimal air flow for your valuable samples.

Mechanical convection

provides even higher temperature uniformity and stability to ensure an optimal environment for your samples. Fan enables fast recovery time after opening the door. A mechanical convection incubator can even be used for drying applications at high temperature settings – eliminating the need for an additional oven.



Select the right model for your needs

Selector Guide

APPLICATION	MATERIAL/ SOLUTION	SAMPLE REQUIREMENTS	RECOMMENDED SOLUTION
Bacterial research	Bacteria	Temperatures between 30 °C and 70 °C	General Protocol Advanced Protocol or Advanced Protocol Security for highest temperature accuracy, and time control
Microbiology	Microorganisms, cells	Temperatures between 30 °C and 50 °C	
Coliform determination	Bacteria	Temperature around 37 °C	
Histology	Tissue	Temperature around 37 °C	
Paraffin embedding	Paraffin	Temperatures of 37 °C to around 50 °C	
Egg incubation	Eggs	Temperature around 37 °C	General Protocol, Advanced Protocol or Advanced Protocol Security for highest temperature accuracy, and time control
Heated storage	Media, samples	Temperature depends on material and specific application – between 30 °C and 105 °C	General Protocol for temperatures up to 75 °C, Advanced Protocol or Advanced Protocol Security for highest temperature accuracy, and time control – up to 105 °C
Gene cloning	Bacteria, cells	Temperature around 37 °C	Advanced Protocol for highest temperature accuracy, and time control
Pharmaceutical stability testing	Various	Temperatures of 37 °C up to 105 °C	Advanced Protocol Security with additional safety features for peace of mind
Food and beverage testing	Various	Temperatures of 37 °C up to 105 °C	
BOD/water pollution testing	Water	Temperature around 20 °C	Compact
Yeast growth	Yeast	Temperatures between 10 °C and 37 °C	General Protocol for temperatures above ambient +5 °C
Hatching of insects, fish	Insects	Temperature near or below ambient	Advanced Protocol or Advanced Protocol Security for highest temperature accuracy or Compact for temperatures as low as 17 °C For lower temperatures check the Thermo Scientific refrigerated models at www.thermoscientific.com/incubators

Footprint Comparison*



Making best use of valuable space in your lab, Heratherm microbiological incubators are designed with a very small footprint ratio compared to the interior volume. In addition they are stackable without the need of any tools or stacking devices.

manufacturer A

manufacturer B

Maximized space efficiency



*based on competitors' published specs; ** optional stacking kit only required if decon cycle or oven is used below, or for stacking different sizes

Thermo Scientific Heratherm Compact Incubator

The most compact unit of the Heratherm microbiological incubator family has an 18L capacity, ideal for personalized workspace.



Heratherm Compact
microbiological incubator, 18L

smart solution for small volume applications

- Minimal footprint for space restricted lab areas
- Temperatures at or below ambient
- High temperature accuracy
- Internal light facilitates sample observation

Easy to use interface



SPECIFICATIONS TABLE/ORDER NUMBERS COMPACT INCUBATORS

Order number	50125882	
Model	IMC18	
Convection technology	Mechanical convection	
Temperature range	°C	17 - 40
Spatial temperature deviation ¹	at 37 °C	± 1.2 °C
Temperature deviation over time	at 37 °C	± 0.2 °C
Footprint	m ² / sqft	0.12 / 1.3
Chamber volume	L / cuft	approx. 18 / 0.65
Dimensions	chamber, mm / in (W x H x D)	180 x 310 x 290 / 7.1 x 12.2 x 11.4
	exterior ² , mm / in (W x H x D)	260 x 415 x 470 / 10.2 x 16.3 x 18.5
Number of shelves	supplied / max	2 / 3
Max. shelf load	kg / lb	2 / 4.4
Rated voltage / frequency	V / Hz	100 - 240 / 50/60
Rated power / max. current	W / A	45 / 0.45 - 0.85
Weight	kg / lb	7.2 / 15.9
Energy consumption at 37 °C	W	14

NOTE: All figures in all tables are typical average values for series devices, based on factory standard following norm Din12880. Please contact us for certification information or IQ/OQ documents.

Thermo Scientific Heratherm General Protocol Incubators

Designed for routine applications in pharmaceutical, medical, food and research laboratories.



Heratherm General Protocol Ovens, 60 L, 100 L, 180 L models



Heratherm microbiological incubators have a smooth inner chamber with easy to clean rounded corners

The flexible shelf system can be removed just with a finger click to easily clean the chamber

intelligent design for improved results

- Gravity convection provides gentle air flow and minimal drying out
- Temperature range from ambient +5 °C up to 75 °C
- Temperature uniformity of ± 0.6 °C
- Temperature stability of ± 0.2 °C
- Corrosion resistant stainless steel chamber (1.4016)

easy to use interface

- Intuitive user interface for easy temperature setting
- Large vacuum fluorescent display for easy reading



SPECIFICATIONS TABLE/ORDER NUMBERS GENERAL PROTOCOL INCUBATORS

Order number		51028130	51028131	51028132
Model		IGS60	IGS100	IGS180
Convection technology		Gravity convection	Gravity convection	Gravity convection
Temperature range	°C	ambient +5 °C to 75 °C	ambient +5 °C to 75 °C	ambient +5 °C to 75 °C
Spatial temperature deviation ¹	at 37 °C	± 0.6 °C	± 0.6 °C	± 0.6 °C
Temperature deviation over time	at 37 °C	± 0.2 °C	± 0.2 °C	± 0.2 °C
Footprint	m ² / sqft	0.3 / 3.2	0.36 / 3.9	0.47 / 5.1
Chamber volume	L / cuft	75 / 2.6	117 / 4.0	194 / 6.85
Dimensions	chamber, mm / in (W x H x D)	354 x 508 x 414 / 13.9 x 20.0 x 16.3	464 x 608 x 414 / 18.3 x 23.9 x 16.3	464 x 708 x 589 / 18.3 x 27.9 x 23.2
	exterior ² , mm / in (W x H x D)	530 x 720 x 565 / 20.9 x 28.3 x 22.2	640 x 820 x 565 / 25.2 x 32.3 x 22.2	640 x 920 x 738 / 25.2 x 36.2 x 29.1
Number of shelves	supplied / max	2 / 13	2 / 16	2 / 19
Max. shelf load	kg / lb	25 / 55	25 / 55	25 / 55
Rated voltage / frequency	V / Hz	230 / 60	230 / 60	230 / 60
Rated power / max. current	W / A	300 / 1.3	520 / 2.3	710 / 3.1
Weight	kg / lb	40 / 88	51 / 112	65 / 143
Energy consumption at 37 °C	W	21	26	31

¹ Values refer to: fan off / fan full speed

² Depth of handle / display not included in depth (65 mm); adjustable feet not included in height (35 mm) – required distance to rear wall: 80 mm

Thermo Scientific Heratherm Advanced Protocol Incubators

Exceptional temperature performance
for demanding applications.

Advanced digital timer

- Turn the unit off at specific time – can be used to interrupt cell growth at specified time: Choose from real time or hour-settings
- Unit is switched on and off at specified time – no need to waste energy when unit is not in use!



Thermo Scientific Heratherm Advanced Protocol microbiological incubator with unique dual convection



design innovation for superior results

- Dual convection for versatility of application: fan speed adjustable from 0 to 100%
- Advanced digital timer for daily or weekly on / off cycles
- Stainless steel interior (1.4301) is easy to clean and corrosion resistant

advanced temperature performance

- Broad temperatures range from 5 °C above ambient to 105 °C – even suitable for drying application
- Temperature uniformity as good as ± 0.2 °C
- Temperature stability at ± 0.1 °C

SPECIFICATIONS TABLE/ORDER NUMBERS ADVANCED PROTOCOL INCUBATORS

Order number (coated exterior)	51028133	51028134	51028135
Model	IMH60	IMH100	IMH180
Order number (stainless steel exterior)	51028717	51028718	51028719
Model	IMH60 SS	IMH100 SS	IMH180 SS
Convection technology	Dual convection	Dual convection	Dual convection
Temperature range	ambient +5 °C to 105 °C	ambient +5 °C to 105 °C	ambient +5 °C to 105 °C
Spatial temperature deviation ¹	at 37 °C $\pm 0.6 / \pm 0.2$ °C	$\pm 0.6 / \pm 0.3$ °C	$\pm 0.6 / \pm 0.4$ °C
Temperature deviation over time	at 37 °C ± 0.1 °C	± 0.1 °C	± 0.1 °C
Footprint	m ² / sqft 0.3 / 3.2	0.36 / 3.9	0.47 / 5.1
Chamber volume	L / cuft 66 / 2.3	104 / 3.67	178 / 6.3
Dimensions	chamber, mm / in (W x H x D) 530 x 720 x 565 / 20.9 x 28.3 x 22.2	464 x 608 x 368 / 18.3 x 23.9 x 14.5 640 x 820 x 565 / 25.2 x 32.3 x 22.2	464 x 708 x 543 / 18.3 x 27.9 x 21.4 640 x 920 x 738 / 25.2 x 36.2 x 29.1
Number of shelves	supplied / max 2 / 13	2 / 16	2 / 19
Max. shelf load	kg / lb 25 / 55	25 / 55	25 / 55
Rated voltage / frequency	V / Hz 230 / 60	230 / 60	230 / 60
Rated power / max. current	W / A 850 / 3.7	1100 / 4.8	1300 / 5.7
Weight	kg / lb 45 / 99	56 / 123	70 / 154
Energy consumption at 37 °C ¹	W 23 / 65	30 / 68	36 / 78



Thermo Scientific Heratherm Advanced Protocol Security Incubators

Incorporates additional safety features for ultimate sample protection.

Heratherm Advanced Protocol Security microbiological incubator with unique dual convection and additional alarm systems



Lockable door for restricted access



140 °C push button decontamination

Building on our established CO₂ incubator decontamination technology, introducing the first microbiological incubators with an independently certified 140 °C decontamination routine⁴.

intelligent design for improved results

superior sample protection

140 °C decontamination

- Lockable incubator door for restricted access
- Audible alarm if the door is left open accidentally



- Automatic over- and under temperature alarm

- At 140 °C contaminating microorganisms are reduced to a minimum, comparable to sterilization, within a six hour cycle
- No need for separate autoclaving of interior fittings
- Certified by an accredited microbiological institute

SPECIFICATIONS TABLE/ORDER NUMBERS ADVANCED PROTOCOL SECURITY INCUBATORS

Order number (coated exterior)	51028136	51028137	51028138
Model	IMH60-S	IMH100-S	IMH180-S
Order number (stainless steel exterior)	51028541	51028542	51028543
Model	IMH60-S SS	IMH100-S SS	IMH180-S SS
Convection technology	Dual convection	Dual convection	Dual convection
Temperature range	ambient +5 °C to 105 °C	ambient +5 °C to 105 °C	ambient +5 °C to 105 °C
Spatial temperature deviation ¹	at 37 °C ± 0.6 / ± 0.2 °C	± 0.6 / ± 0.3 °C	± 0.6 / ± 0.4 °C
Temperature deviation over time	at 37 °C ± 0.1 °C	± 0.1 °C	± 0.1 °C
Footprint	m ² / sqft 0.3 / 3.2	0.36 / 3.9	0.47 / 5.1
Chamber volume	L / cuft 66 / 2.3	104 / 3.67	178 / 6.3
Dimensions	chamber, mm / in (W x H x D) 354 x 508 x 368 / 13.9 x 20.0 x 14.5	464 x 608 x 368 / 18.3 x 23.9 x 14.5	464 x 708 x 543 / 18.3 x 27.9 x 21.4
	exterior ² , mm / in (W x H x D) 530 x 720 x 565 / 20.9 x 28.3 x 22.2	640 x 820 x 565 / 25.2 x 32.3 x 22.2	640 x 920 x 738 / 25.2 x 36.2 x 29.1
Number of shelves	supplied / max 2 / 13	2 / 16	2 / 19
Max. shelf load	kg / lb 25 / 55	25 / 55	25 / 55
Rated voltage / frequency	V / Hz 230 / 60	230 / 60	230 / 60
Rated power / max. current	W / A 1390 / 6.1	1390 / 6.1	1390 / 6.1
Weight	kg / lb 45 / 99	56 / 123	70 / 154
Energy consumption at 37 °C ³	W 23 / 65	30 / 68	36 / 78

¹ Values refer to: fan off / fan full speed

² Depth of handle / display not included in depth (65 mm); adjustable feet not included in height (35 mm) – required distance to rear wall: 80 mm

³ Height of stand including casters: 187 mm

⁴ verified by independent testing facility (BBE 9/2010)

Thermo Scientific Heratherm

Large Capacity Incubators

General Protocol Models

Designed with your need for high sample volume or larger samples in mind.



Thermo Scientific Heratherm large capacity incubators are available as 400 L and 750 L units.

400 L

750 L

efficiency

- Two sizes (400 and 750 L)
- Gravity convection technology with unique air flow – designed for minimal drying out of samples
- Flexible shelf system for optimal use of chamber volume

safety

- Automatic overtemperature alarm system to protect samples – no need for timely manual setting
- Inner glass door for undisturbed viewing of samples
- Inner chambers made from corrosion-resistant stainless steel (1.4016)
- Protect delicate samples with stable temperature conditions: uniformity of up to ± 0.5 °C and temperature stability of 0.4 °K at 37 °C



180°

180° door opening allows convenient access to the interior for hassle free cleaning and easy loading of probes.

Easy to view, vacuum fluorescence display with push-button simplicity



Lockable casters for easy set-up and moving



maximum convenience

- Large, easy to view, vacuum fluorescence display with simple to use touch button operation controlled by an onboard microprocessor
- Doors can be opened over 180 ° for easy access and use
- Inner chamber in stainless steel and with rounded edges for easy cleaning
- Lockable casters for easy mobility and stability
- Standard access port can be used for independent data monitoring

SPECIFICATIONS TABLE/ORDER NUMBERS LARGE CAPACITY GENERAL PROTOCOL INCUBATORS

Order number		51029322	51029334
Model		IGS400	IGS750
Convection technology		gravity convection	gravity convection
Temperature range	°C	ambient +5°C to 75°C	ambient +5°C to 75°C
Spatial temperature deviation	at 37 °C	± 0.5°C	± 1.3 C
Temperature deviation over time	at 37 °C	± 0.4°C	± 0.4 C
Footprint	m ² / sqft	0.56 / 6.0	0.91 / 9.8
Chamber volume	l / cuft	405 / 14.3	747 / 26.4
Dimensions	chamber mm / in (W x H x D)	544 x 1307 x 569 / 21.4 x 51.5 x 22.4	1004 x 1307 x 569 / 39.5 x 51.5 x 22.4
	exterior ¹ mm / in (W x H x D)	778 x 1545 x 770 / 30.6 x 60.8 x 30.3	1261 x 1545 x 770 / 49.6 x 60.8 x 30.3
Number of shelves	supplied/max	2 / 39	2 / 39
Max. shelf load	kg / lb	30 / 66	30 / 66
Rated voltage / Frequency	V / Hz	230 / 50/60	230 / 50/60
Rated power / Max current	W / Amp	1200 / 5.0	1500 / 6.5
Weight	kg / lb	145 / 320	201 / 443
Energy consumption at 37 °C	W	55	80

¹ Depth of handle / display not included in depth (65 mm); casters not included in height (108 mm) – required distance to rear wall: 120 mm
 NOTE: All figures in all tables are typical average values for series devices, based on factory standard following norm Din12880.
 Please contact us for certification information or IQ/OQ documents.

Thermo Scientific Heratherm

Advanced Protocol Security Incubators

Mechanical convection technology provide unsurpassed temperature uniformity and stability to ensure fully reproducible results. An extensive range of additional features is ensuring even more flexibility, accuracy and dependability.




prime performance

- Mechanical convection technology ensures optimal temperature distribution with improved level of temperature uniformity: ± 0.2 to 0.3 °C
- Temperature range from ambient $+5$ °C to 105 °C for application flexibility: units can even be used for drying applications

added safety

- Unique 140°C decontamination cycle eliminating the need for separate autoclaving or use of toxic decontaminants
- 2-speed fan for application flexibility:
 - > Slow speed for incubation applications that require reduced drying out
 - > High speed for best temperature uniformity and stability
- An additional undertemp alarm provides safety even in case the temperature deviates below setpoint
- Door alarm notifies operator in case the door is left open



Advanced protocol security units available in stainless steel exterior.



Access port for independent sensor or use of shaker / stirrer inside the unit



Two speed fan for matching the airflow to your application

Additional features

- Best temperature performance and unique certified decontamination cycle.



enhanced efficiency

- Sophisticated timer extends the automation options available to the user
 - > Choose between a simple on/off timer, recurring weekly timer or set incubator activity based on the 24 hour clock
- Inner chamber made from stainless steel (highly resistant quality 1.4301)

SPECIFICATIONS TABLE/ORDER NUMBERS LARGE CAPACITY ADVANCED PROTOCOL SECURITY INCUBATORS

Order number (coated exterior)	51029325	51029337
Model	IMH400-S	IMH750-SS
Order number (stainless steel exterior)	51029326	51029338
Model	IMH400-S SS	IMH750-S SS
Convection technology	mechanical convection	mechanical convection
Temperature range	ambient +5°C to 105°C	ambient +5 to 105
Spatial temperature deviation	at 37 °C ± 0.2 °C	± 0.3
Temperature deviation over time	at 37 °C ± 0.2 °C	± 0.2
Footprint	0.56 / 6.0	0.91 / 9.8
Volume of workspace	381 / 13.5	702 / 24.8
Dimensions	chamber mm / in (W x H x D) exterior ¹ mm / in (W x H x D)	544 x 1335 x 524 / 21.4 x 52.6 x 20.6 778 x 1545 x 770 / 30.6 x 60.8 x 30.3
Number of shelves	supplied / max	2 / 39
Max. shelf load	kg / lb	30 / 66
Rated voltage / Frequency	V / Hz	230 / 50/60
Rated power / Max current	W / Amp	1400 / 6.0
Weight	kg / lb	205 / 452
Energy consumption at 37 °C	W	87

¹ Depth of handle / display not included in depth (65 mm); casters not included in height (180 mm) – required distance to rear wall: 120 mm
NOTE: All figures in all tables are typical average values for series devices, based on factory standard following norm Din12880.
Please contact us for certification information or IQ/OQ documents.

Stainless Steel Exterior

An optional stainless steel exterior is available for the Advanced Protocol and Advanced Protocol Security models.



Heratherm Advanced Protocol Security microbiological incubators with stainless steel exterior

Maximized performance:

- Robust and corrosion-resistant surface
- Easy to clean
- Meets demanding needs in pharmaceutical and clinical laboratories



Proven Results

Heratherm incubators offer superior data monitoring systems that provide the key to reliable results.



RS232 standard on all GP, AP, and APS models/sizes

Check the unique optional sample sensor for Advanced Protocol Security models:

- Measure exact sample temperature, shown on display in addition to chamber temperature
- Additional peace of mind for safety of your precious samples
- Easy connection at rear of unit



data monitoring capabilities

- All models have an access port
 - > Ideal for insertion of an independent sample temperature sensor, for Good Laboratory Practice (GLP) compliance
 - > Large diameter of 42 / 1.65 (38 / 1.1)* mm/inches fits standard plug
 - > Covered by stopper to prevent any temperature disturbance
- All models incorporate a standard RS232 interface
- Advanced Protocol Security models include socket for independent sample sensor (option):
When connected, exact sample temperature is shown on display

* General Protocol large capacity units only

Accessories

SPECIFICATIONS TABLE/ORDER NUMBERS

DESCRIPTION	ORDER NUMBER	DETAILS
Perforated shelves		
Perforated shelf Compact	50125605	Stainless steel perforated shelf for Compact incubator; 180 x 290 mm
Perforated shelf General Protocol 60 L	50127770	Stainless steel perforated shelf for General Protocol 60 L; including 2 shelf supports; 329 x 376 mm
Perforated shelf General Protocol 100 L	50127771	Stainless steel perforated shelf for General Protocol 100 L; including 2 shelf supports; 439 x 376 mm
Perforated shelf General Protocol 180 L	50127772	Stainless steel perforated shelf for General Protocol 180 L; including 2 shelf supports; 439 x 551 mm
Perforated shelf Advanced Portocol / Advanced Protocol Security 60 L	50127773	Stainless steel perforated shelf for Advanced Portocol / Advanced Protocol Security; 60 L; including 2 shelf supports; 329 x 330 mm
Perforated shelf Advanced Portocol / Advanced Protocol Security 100 L	50127774	Stainless steel perforated shelf for Advanced Portocol / Advanced Protocol Security; 100 L; including 2 shelf supports; 439 x 330 mm
Perforated shelf Advanced Portocol / Advanced Protocol Security 180 L	50127777	Stainless steel perforated shelf for Advanced Portocol / Advanced Protocol Security; 180 L; including 2 shelf supports; 439 x 505 mm
Perforated Shelf 400 L	50135241	Stainless steel perforated shelf for General Protocol and Advanced Protocol Security 400 L; including 2 shelf supports; 528 x 498 mm
Perforated Shelf 750 L	50135242	Stainless steel perforated shelf for General Protocol and Advanced Protocol Security 750 L; including 2 shelf supports; 984 x 498 mm
Additional shelving		
Wire mesh shelf 60 L	50127764	Wire mesh shelf for Advanced Portocol / Advanced Protocol Security; 60 L; including 2 shelf supports; 338 x 336 mm
Wire mesh shelf 100 L	50127765	Wire mesh shelf for Advanced Portocol / Advanced Protocol Security; 100 L; including 2 shelf supports; 448 x 336 mm
Wire mesh shelf 180 L	50127766	Wire mesh shelf for Advanced Portocol / Advanced Protocol Security; 180 L; including 2 shelf supports; 448 x 511 mm
Wire mesh shelf 750 L	50135044	Wire mesh shelf for Advanced Protocol Security; 750 L; including 2 shelf supports; 984 x 513 mm
Petri Dish holder (90 mm) 60 L	50128816	Shelf with holders for Petri dishes; ø 90 mm; stainless steel; for all 60 l incubators; incl. 2 shelf supports; 9 stacks; 77 mm height
Petri Dish holder (90 mm) 100 L	50128817	Shelf with holders for Petri dishes; ø 90 mm; stainless steel; for all 100 l incubators; incl. 2 shelf supports; 12 stacks; 77 mm height
Petri Dish holder (90 mm) 180 L	50128819	Shelf with holders for Petri dishes; ø 90mm; stainless steel; for all 180 l incubators; incl. 2 shelf supports; 16 stacks; 77 mm height
Petri Dish holder (50 mm) 60 L	50128793	Shelf with holders for Petri dishes; ø 50mm; stainless steel; for all 60 l incubators; incl.2 shelf supports; 20 stacks; 77 mm height
Petri Dish holder (50 mm) 100 L	50128794	Shelf with holders for Petri dishes; ø 50mm; stainless steel; for all 100 l incubators; incl. 2 shelf supports; 24 stacks; 77 mm height
Petri Dish holder (50 mm) 180 L	50128815	Shelf with holders for Petri dishes; ø 50mm; stainless steel; for all 180 l incubators; incl. 2 shelf supports; 36 stacks; 77 mm height
Drip Tray 60 L	50128683	Stainless steel drip tray for all 60 l incubators; includes 2 shelf supports; 295 x 325 x 20 mm drip space
Drip Tray 100 L	50128791	Stainless steel drip tray for all 100 l incubators; includes 2 shelf supports; 405 x 325 x 20 mm drip space
Drip Tray 180 L	50128792	Stainless steel drip tray for all 180 l incubators; includes 2 shelf supports; 405 x 500 x 20 mm drip space
Lowenstein kit	50128265	Lowenstein kit 150 mm tubes; 2 trays to place on top of perforated shelf (shelf not supplied); 435 x 155 mm; 20 tubes each tray – usable for 100 L models and larger
Silicone free viton door sealing		
Silicone free viton sealing 60 L	50130657	Silicone free viton door sealing for all 60 liter Heratherm incubators
Silicone free viton sealing 100 L	50130658	Silicone free viton door sealing for all 100 liter Heratherm incubators
Silicone free viton sealing 180 L	50130659	Silicone free viton door sealing for all 180 liter Heratherm incubators
Silicone free viton sealing 400 L	50135869	Silicone free viton door sealing for all 400 liter Heratherm incubators
Silicone free viton sealing 750 L	50135870	Silicone free viton door sealing for all 750 liter Heratherm incubators



Stainless steel perforated shelves



Petri dish holder



Drip tray



Lowenstein shelves



Silicone free viton door sealing

Thermo Scientific Heratherm Microbiological Incubators

Thermo Scientific Smart-Vue Wireless Monitoring

Smart. Scalable. Simple.

Continuously monitors sample environment

- Secure data logging with real-time alarms
- Audit trail traceability to assist with conformance to 21 CFR Part 11

To learn more, visit
www.thermoscientific.com/smart-vue

Solutions vary by RF regions worldwide and are compatible with multiple brands and types of laboratory equipment. Contact your local sales representative for more details.



Rear view of the 100 L Advanced Protocol oven with Smart-Vue



thermoscientific.com/incubators

© 2012 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Africa-Other +27 11 570 1840
Australia +61 2 8844 9500
Austria +43 1 333 50 34 0
Belgium +32 53 73 42 41
Canada +1 800 530 8447
China +86 10 8419 3588
Denmark +45 70 23 62 60
Europe-Other +43 1 333 50 34 0

Finland /Norway/Sweden
+46 8 556 468 00
France +33 1 60 92 48 00
Germany +49 6184 90 6000
India +91 22 6742 9434
Italy +39 02 95059554
Japan +81 45 453 9100
Latin America +1 608 276 5659

Middle East +43 1 333 50 34 0
Netherlands +31 76 579 55 55
South Africa +27 11 570 1840
Spain +34 914 845 965
Switzerland +41 44 454 12 22
UK +44 1442 233555
USA +1 800 532 4752

Thermo
SCIENTIFIC

Part of Thermo Fisher Scientific