



## LABORHITS

## uniPLATESHAKER 1

Variable speed from 300 to 1800 rpm

Suitable for use in cold-rooms

Very small footprint

## **Features**

- Universal fit, comes with interchangeable clamps for different micro plate sizes
- Digital Display with Speed and Time settings
- Maintenance free brushless DC motor
- Orbital Diameter of 2 mm for thorough mixing
- Timer setting from 1 to 99 min and continuous mode
- Comes with foam attachment for 20 x 1.5/2 ml microtubes
- 3-years warranty

The LLG-uniPLATESHAKER 1 has been designed for accommodating and mixing a single micro plate. Due to its small footprint it can be used in working areas with limited space such as fume hoods and bio safety cabinets.

Туре	Cat. No.
uni <i>PLATESHAKER</i> 1 with EU-plug	6.263 488
uniPLATESHAKER 1 with UK-plug	6.263 489



Specifications

Type of movement: orbital Orbital diameter: 2 mm Speed range: 300 - 1800 rpm Motor: Brushless DC motor Timer: 1 - 99 min, continuous Power consumption: 15 W

Permissible ambient temperature: 4 - 40 °C Dimensions (W x D x H): 127 x 85 x 86 mm

Weight: 1.4 kg

Power supply: 100 - 230 V, 50/60 Hz