

LABORHITS

Pharmacy refrigerators MK



Safe storage of sensitive medications

Visible and audible signal at cold deviation

Liebherr pharmaceutical refrigerators compliant with DIN 58345 safely store high-quality preparations and sensitive medications at all times. This is achieved by a combination of precise electronic controls, highly effective insulation, an optimised forced-air cooling system, and premium-quality workmanship.

Features

- Operating temperature from +2 °C to +8 °C
- Visual and audible warning installation for high and low temperature
- Safety thermostat to avoid temperatures below +2 °C
- Visual and audible power failure alarm for at least 12 h
- Can be used in ambient temperatures from +10 °C to +35 °C
- Noise emission less than 60 dB(A)
- Mechanical resistance of internal fittings at least 100 kg/m²
- Lockable door optionally made of steel or insulating glass

Type	Capacity l	External dimensions mm (W x D x H)	Internal dimensions mm (W x D x H)	Energy consumption kWh (24h)	Temperature °C	Weight kg	PK	Cat. No.
1 MKv 3910-21	360	600 x 615 x 1840	440 x 435 x 1635	0.846	5	74	1	6.283 694
2 MKv 3913-20*	360	600 x 615 x 1840	440 x 435 x 1635	1.315	5	91	1	6.283 866
3 MKUv 1610-21	141	600 x 615 x 820	440 x 435 x 670	0.747	5	41	1	6.283 386
4 MKUv 1613-20*	141	600 x 615 x 820	440 x 435 x 670	1.010	5	46	1	6.283 865

*with isolation glass door with switchable LED illumination