

AUTO

106

Core temperature thermometer

testo 106 - The compact food thermometer

Ideal for use in the food sector

TopSafe: dishwasher-safe protective cover (IP67), protects from dirt and impact

Small, handy and always ready to hand

Audible and optical alarm

Automatic final value recognition (Auto-hold)

Hardly visible punctures

Certified according to EN 13485 (only in combination with TopSafe)



The core thermometer testo 106 is especially fast and robust. Its small handy shape means it is always close to hand and ready for use. Thanks to its very thin and robust measurement tip, it is excellently suited to core temperature checks in gastronomy, hotels, large kitchens, supermarkets etc. The dishwasher-safe TopSafe protects the instrument from dirt, water and impact. The testo 106 is comform to HACCP as well as EN 13485. If required, upper and lower limit values can be stored in the instrument; as soon as these values are violated, audible and optical warning signals are given. This alarm function and the automatic final value recognition facilitate measurement and support you in recognizing and interpreting measurement values quickly and correctly.

Technical data / Accessories

	Sensor type	NTC
sto 106	Measuring range	-50 to +275 °C
106, food core thermometer incl. probe ecting cap, battery and calibration protocol	Accuracy ±1 digit	±1 % of m.v. (+100 to +275 °C) ±0.5 °C (-30 to +99.9 °C) ±1 °C (-50 to -30.1 °C)
orecting cap, battery and calibration protocol	Resolution	0.1 °C
	General technica	l data
rt no. 0560 1063	Storage temperature	-40 to +70 °C
	Operating temperature	-20 to +50 °C
	t ₉₉	10 s
	Battery type	3V button cell (CR 2032)
	Battery life	350 h
	Weight	80 g
testo 106	Dimensions Length Probe shaft / Probe shaft tip	215 x 34 x 19 mm 55 mm / 15 mm
o 106, food core thermometer incl. 9 (waterproof protection case, IP67, 19 tent clip, probe protection cap, battery bration protocol	Diameter Probe shaft / Probe shaft tip	Ø 3 mm / Ø 2.2 mm
	Display	LCD, 1 line
0563 1063	Housing material	ABS
	Protection class	IP 67 with TopSafe

Accessories

Accessories for measuring instrument		
TopSafe (indestructible protection case); waterproof and dishwasher-safe protection case (IP67)	0516 8265	
Holding clip with probe protection cap	0554 0825	
ISO calibration certificate/temperature ; for air/immersion probes, calibration point +60°C	0520 0063	
ISO calibration certificate/temperature ; for air/immersion probes, calibration point -18°C	0520 0061	
ISO calibration certificate/temperature ; for air/immersion probes, calibration point 0°C	0520 0062	
ISO calibration certificate/temperature ; for air/immersion probes, calibration points -18°C; 0°C	0520 0041	
ISO calibration certificate/temperature ; for air/immersion probes, calibration points -8°C; 0°C; +40°C	0520 0181	


Warranty

Standard

2 years

EN 13485

Part no.



0981 9494/msp/A/01.2016